Serial No. 10/541,061

December 14, 2009

**AMENDMENTS TO THE CLAIMS:** 

The following listing of claims supersedes all prior versions and listings of claims

in this application:

1. (Currently Amended) A distributed storage network comprising a plurality of

interconnected computers, said computers including a plurality of host computers and at

least one client computer, wherein said client computer stores client code comprising:

a) storage initiation code executable to initiate storage of a data item on one or

more of said plurality of host computers;

b) storage condition generation code executable to generate one or more

interpretable storage conditions indicating characteristics of host computers suitable for

storing said data item;

c) storage condition sending code executable to send said one or more

interpretable storage conditions to one or more of said host computers;

d) storage condition reception code executable to receive said one or more

interpretable storage conditions from said client computer or another of said host

computers;

wherein each of said host computers stores host code including:

- 2 -

1567727

Derrick D. ROBERTSON, et al. Serial No. 10/541,061 December 14, 2009

[[c)]] e) host computer characteristic provision code executable to measure and then provide host storage characteristic data indicating one or more characteristics of one or more memories of said host computer;

[[d)]] <u>f)</u> condition interpreter code executable to interpret said one or more interpretable storage conditions in the light of said one or more host <u>storage</u> characteristics provided by said host computer and thereby to establish whether <u>one or more memories of</u> said host computer meets said storage conditions;

[[e)]] <u>g)</u> data item storage code executable to store said data item in said host computer on the execution of said condition interpreter code finding that said <u>one or more memories of said</u> host computer meets said requirements; and

f) data item h) storage condition forwarding code executable, on the execution of said condition interpreter code finding that the one or more memories of said host computer does not meet said conditions, to forward said data item and said storage condition to another of said host computers.

## 2-4. (Cancelled)

5. (Original) A distributed storage network according to claim 1 in which at least one of said computers stores both said client code and said host code.

Serial No. 10/541,061

December 14, 2009

6. (Previously Presented) A distributed storage network according to claim 1 in

which said one or more interpretable storage conditions are persistently stored at one or

more of said computers.

7. (Original) A distributed storage network according to claim 6 wherein said

persistent storage is provided by a database stored at each of said one or more

computers providing persistent storage of said interpretable storage conditions.

8. (Previously Presented) A distributed storage network according to claim 6 in

which one or more computers further stores condition editor code executable to provide

a user with an interface enabling the user to update said interpretable storage

conditions or to record new interpretable storage conditions.

9. (Original) A distributed storage network according to claim 8 in which said

client computer further stores said condition editor code.

10. (Original) A distributed storage network according to claim 1 in which said

condition interpreter code interprets said one or more interpretable storage conditions

using schema data which indicates a common structure for said interpretable storage

conditions.

-4-

Serial No. 10/541,061 December 14, 2009

11. (Previously Presented) A distributed storage network according to claim 1 in

which said interpretable storage conditions form a component of a rules data structure

which further includes action data indicating actions to be carried out by one of said

computers on said host computer meeting said storage condition.

12. (Original) A distributed storage network according to claim 11 in which said

rules data structure forms a component of a policy data structure which further includes

event data indicating one or more events which must take place in order to trigger the

execution of said condition interpreter code.

13. (Previously Presented) A distributed storage network according to claim 1 in

which said host computer characteristics include stored data item description data

which describes data items already stored at said host computer.

14. (Previously Presented) A distributed storage network according to claim 1 in

which said interconnected computers comprise computers having differing hardware

architectures and operating system programs stored thereon, each of said computers

further storing common machine emulation code executable to translate code

- 5 -

Serial No. 10/541,061 December 14, 2009

executable on said common machine to code executable on the hardware architecture and operating system of the machine on which the emulation code is executed.

15. (Currently Amended) A distributed storage network comprising:

a plurality of interconnected computers, each computer being operable to store data in one or more memories under the control of said computer;

each of said computers having access to processor executable code, said code comprising:

- a) data item reception code processable to receive a data item;
- b) data item storage requirements discovery code processable to find one or more requirements relating to said data item;
- c) storage information provision code processable to measure and then provide storage information concerning one or more memories of said computer;
- d) storage condition sending code executable to send said storage information to one or more other of said computers;
- e) storage condition reception code executable to receive said storage information from one or more other of said computers;
- [[d)]] <u>f)</u> comparison code processable to compare said data item storage requirements with said storage information provided by said computer;

Serial No. 10/541.061

December 14, 2009

[[e)]] g) storage decision code processable to decide whether to store said data

item in said one or more memories in dependence upon said comparison; and

[[f)]] h) data item storage code processable to store said data item at said host

computer on execution of said storage decision code finding that said computer meets

said storage conditions; and

g) data item i) storage condition forwarding code executable to forward said data

item and said storage condition to another of said host computers on execution of said

storage decision code finding that said computer does not meet said storage conditions.

16. (Currently Amended) A method of operating a network of interconnected

computers, said computers including a plurality of host computers and a least one client

computer, said method including the steps of:

operating said client computer to:

a) initiate storage of a data item on one or more of said plurality of host

computers; and

b) generate one or more interpretable storage conditions indicating

characteristics of host computers suitable for storing said data item;

c) send said one or more interpretable storage conditions to one or more of said

host computers;

- 7 -

Serial No. 10/541,061 December 14, 2009

d) receive said one or more interpretable storage conditions from said client computer or another of said host computers;

operating said host computer to:

[[c)]] <u>e)</u> measure and then provide host characteristic data indicating one or more characteristics of said host computer;

[[d)]] <u>f)</u> interpret said one or more interpretable storage conditions in the light of said one or more host characteristics provided by said host computer and thereby to establish whether said host computer meets said storage conditions;

[[e)]] g) store said data item at said host computer on finding that said host computer meets said storage conditions; and

[[f)]] h) forward said data item and said storage condition to another of said host computers on finding that the host computer does not meet said conditions.

- 17. (Original) A computer readable storage medium storing code executable to carry out method steps a) and b) of claim 16.
- 18. (Original) A computer readable storage medium storing code executable to carry out method steps c), d) and e) of claim 16.

Serial No. 10/541,061

December 14, 2009

19. (Original) A computer readable storage medium storing code executable to

carry out the method steps of claim 16.

20. (Currently Amended) A host computer configured to be part of a distributed

storage network comprising a plurality of interconnected computers including a plurality

of host computers and at least one client computer storing client code including storage

initiation code executable to initiate storage of a data item on one or more of said

plurality of host computers and storage condition generation code executable to

generate one or more interpretable storage conditions indicating characteristics of host

computers suitable for storing said data item, said host computer storing host code

including:

a) host computer characteristic provision code executable to measure and then

provide host characteristic data indicating one or more characteristics of said host

computer;

b) storage condition sending code executable to send said one or more

interpretable storage conditions to one or more of said host computers;

c) storage condition reception code executable to receive said one or more

interpretable storage conditions from said client computer or another of said host

computers;

- 9 -

Serial No. 10/541,061

December 14, 2009

[[b)]] d) condition interpreter code executable to interpret said one or more interpretable storage conditions in the light of said one or more host characteristics provided by said host computer and thereby to establish whether said host computer meets said storage conditions;

[[c)]] e) data item storage code executable to store said data item in said host computer on the execution of said condition interpreter code finding that said host computer meets said requirements; and

[[d)]] <u>f)</u> data item <u>storage condition</u> forwarding code executable, on the execution of said condition interpreter code finding that the host computer does not meet said conditions, to forward <u>said data item and</u> said storage condition to another of said host computers.

21. (Currently Amended) A method of operating a host computer configured to be part of a distributed storage network comprising a plurality of interconnected computers including a plurality of host computers and at least one client computer storing client code including storage initiation code executable to initiate storage of a data item on one or more of said plurality of host computers and storage condition generation code executable to generate one or more interpretable storage conditions indicating characteristics of host computers suitable for storing said data item, said method comprising:

Serial No. 10/541,061 December 14, 2009

a) executing host computer characteristic provision code to measure and then provide host characteristic data indicating one or more characteristics of said host computer;

b) storage condition sending code executable to send said one or more interpretable storage conditions to one or more of said host computers;

c) storage condition reception code executable to receive said one or more interpretable storage conditions from said client computer or another of said host computers;

[[b)]] <u>d)</u> executing condition interpreter code to interpret said one or more interpretable storage conditions in the light of said one or more host characteristics provided by said host computer and thereby to establish whether said host computer meets said storage conditions;

[[c)]] <u>e)</u> executing data item storage code to store said data item in said host computer on the execution of said condition interpreter code finding that said host computer meets said requirements; and

[[d)]] <u>f)</u> executing <u>data item</u> <u>storage condition</u> forwarding code, on the execution of said condition interpreter code finding that the host computer does not meet said conditions, to forward <u>said data item and</u> said storage condition to another of said host computers.

Serial No. 10/541,061

December 14, 2009

22. (New) A distributed storage network as in claim 1 wherein the data item is forwarded with the storage condition in step h).

23. (New) A method as in claim 15 wherein the data item is forwarded with the storage condition in step i).

24. (New) A method as in claim 16 wherein the data item is forwarded with the storage condition in step h).

25. (New) A host computer as in claim 20 wherein the data item is forwarded with said storage condition in step f).

25. (New) A method as in claim 21 wherein the storage condition is forwarded with said data item in step f).